

SCHEDULED MAINTENANCE CHECK SHEET

(all models with 6,000 mile (10,000 km) service intervals)



Customer Name	Registration Number	Model	Date
Date of Registration	VIN	Odometer Reading	Job Number
Bike Under Warranty? <input type="checkbox"/> Yes <input type="checkbox"/> No	Service Book Stamped? <input type="checkbox"/> Yes <input type="checkbox"/> No	Technician Name	Technician Signature

Carry out all the operations specified below at the required intervals. Additional operations must be carried out at the specified time/distance interval, whichever comes first.

IMPORTANT: Under severe operating conditions, certain items require more frequent servicing. Refer to the Owner's Handbook for further information.

6,000 mile (10,000 km) service intervals (All models except Trophy, Trophy SE, Tiger Explorer, Rocket III, Rocket III Classic, Rocket III Touring & Rocket III Roadster)			
First Service - First 500 miles / 800 km / 1 Month (whichever comes first)	Annual Service - Every year	Additional items at specified mileage/date only, as indicated below	

First Service	<input checked="" type="checkbox"/>	Tick Box when Item Complete
Annual Service	<input type="checkbox"/>	Not Applicable to this Model
6,000 and 18,000 miles (10,000 and 30,000 km)	<input type="checkbox"/>	
12,000 miles (20,000 km)	<input type="checkbox"/>	
24,000 miles (40,000 km)	<input type="checkbox"/>	

Lubrication				
				1. Engine oil - renew
				2. Engine oil filter - renew
				3. Engine & oil cooler - check for leaks
Fuel System and Engine Management				
				1. Throttle cables - check/adjust
				2. Fuel system - check for leaks, chafing
				3. Throttle body plate (butterfly) - check/clean
				4. Autoscanner - Carry out a full Autoscanner using the Triumph diagnostic tool (print a customer copy)
				5. Engine, Immobiliser and ABS ECMs - check for stored DTCs
				6. Secondary exhaust clamp bolts - check/adjust torque (675 cc and 1050 cc engines only)
				7. Idle CO level - check/adjust (carburettor and open loop EFI models only)
				8. Air cleaner - renew
				9. Fuel filter - renew (if fitted)
				10. Throttle bodies/carburettors - balance
				11. Fuel hoses - renew - every 4 years, regardless of mileage †
				12. Secondary air injection system - check/clean
				13. Evaporative hoses - renew (if fitted) - every 4 years, regardless of mileage †
				14. Exhaust butterfly valve cables - check/adjust (Daytona 675, Thunderbird Commander and Thunderbird LT only)
				15. Exhaust butterfly valve actuator - check/clean/grease electrical connector (Daytona 675, Thunderbird Commander and Thunderbird LT only) - except first service
Ignition System				
				1. Spark plugs - check
				2. Spark plugs - renew
Cooling System (liquid cooled models only)				
				1. Cooling system - check for leaks
				2. Coolant level - check/adjust
				3. Coolant - renew - every 3 years, regardless of mileage †
Engine				
				1. Clutch cable - check/adjust
				2. Valve clearances - check/adjust †
				3. Camshaft timing - adjust - only first 12,000 miles (20,000 km) service (Tiger 800, Tiger 800XC from VIN 601012, Daytona 675 from VIN 564948 and Street Triple from VIN 560477 only)
Wheels and Tyres				
				1. Wheels - inspect for damage
				2. Wheel bearings - check for wear/smooth operation
				3. Wheels - check for broken or damaged spokes and check spoke tightness (not alloy wheels)
				4. Tyre wear/tyre damage - check
				5. Tyre pressures - check/adjust
Electrical				
				1. Lights, instruments & electrical systems - check

First Service	<input checked="" type="checkbox"/>	Tick Box when Item Complete
Annual Service	<input type="checkbox"/>	Not Applicable to this Model
6,000 and 18,000 miles (10,000 and 30,000 km)	<input type="checkbox"/>	
12,000 miles (20,000 km)	<input type="checkbox"/>	
24,000 miles (40,000 km)	<input type="checkbox"/>	

Steering and Suspension				
				1. Steering - check for free operation
				2. Forks - check for leaks/smooth operation
				3. Fork oil - renew
				4. Headstock bearings - check/adjust - except first service
				5. Headstock bearings - lubricate
				6. Rear wheel bearings - lubricate (single-sided swinging arm models only)
				7. Rear suspension unit and linkage - check/lubricate (single rear suspension unit models only)
Brakes				
				1. Brake pads - check wear levels ‡
				2. Brake master cylinders - check for fluid leaks
				3. Brake calipers - check for fluid leaks and seized pistons
				4. Brake fluid levels - check
				5. Brake fluid - renew - every 2 years, regardless of mileage †
Drive Chain and Drive Belt				
				1. Drive belt - inspect for wear or damage
				2. Drive belt tension - check and adjust annually or every 2,500 miles (4,000 km) whichever comes first
				3. Drive flange bearings - check for wear/smooth operation (drive belt models only)
				4. Drive flange assembly - renew (drive belt models only) ¹
				5. Drive chain slack - check/adjust
				6. Drive chain - wear check ‡
				7. Drive chain - lubricate
				8. Drive chain rubbing strip - check ‡
				9. Drive chain rubbing strip - renew
General				
				1. Fasteners - inspect visually for security
				2. Accessory rack sliding carriage - check for correct operation - except first service
				3. Accessory pannier link bar - check for correct operation and adjustment
				4. Centre and/or side stand - check operation
				5. Carry out all outstanding service bulletin and warranty work
				6. Carry out road test
				7. Complete the service record book and reset the service indicator (if fitted)

Note:

The following notes must be referred to as necessary during scheduled servicing:

‡ Renew checked items if worn beyond the service limit.

§ Tiger 800 and Tiger 800XC only.

† **Additional** items are subject to additional labour charge, above the cost and time allowance for the basic service, which includes time to check only.

¹ **For Thunderbird motorcycles up to VIN 454618 only:** Renew the drive flange assembly (part number T2010461) at the **first** 24,000 miles (40,000 km) service only. At subsequent services, check the drive flange bearings for wear/smooth operation.

Daily checks must also be carried out as specified in the Owner's Handbook.